



Manufactured by an
ISO 9001
2015
Certified Company

Elastomeric Waterproofing Paint



WATERPROOFING
HAIRLINE CRACKS



HIGH FLEXIBILITY



HIGHLY RESISTANT
TO FUNGUS & ALGAE



UV RESISTANT



WATERPROOFING
COATING

DESCRIPTION

CeyaKrete AquaShield is a superior waterproofing paint which has been manufactured in compliance to ISO 9001:2015 quality management process using internationally certified high quality raw materials. It is an easy to apply, long-lasting and non-peeling coating. CeyaKrete AquaShield also prevents moisture leakage through hairline cracks.

USES

- Waterproofing for walls open to rain exposure
- Bathroom walls
- Cement roofing sheets
- Blind Walls
- etc.

FEATURES

- Stop water penetration from hairline cracks
- High Flexibility
- Highly Resistant to Fungus & Algae
- UV Resistant

INSTRUCTIONS FOR USE

SURFACE PREPARATION

All the substrates must be dry and free of dust, dirt, moss, oil, grease and loose particles. Ensure that there is good ventilation on the surface.

APPLICATION

Stir the contents prior to the application to remove any sediment. AquaShield paints can be applied using soft bristled brushes. Ensure that each coat is completely dry before applying the next coat. A close visual inspection of the surface should be made for any pin holes or surface irregularities before applying the second coat. The second coat should be applied at the right angle to the first at the same coverage rate. Application of third coat is necessary for highly damping areas and water gathering areas.

DILUTION:

clean potable water
1st coat - 3 parts paint : 1 part water
2nd coat - 4 parts paint : 1 part water
3rd coat - 4 parts paint : 1 part water

COVERAGE:

40 - 50 Sqft/Lit. for 2 Coats
(Depending on surface condition).

CERTIFICATION:

ISO 9001:2015 Quality Management System and Certified Test Reports.

DRYING TIME:

4 - 6 hours between coats.

Do not apply when rain or dew is forecast within 24 hours or temperature falls below 18°C or above 30°C.

STORAGE AND SHELF LIFE:

Store under cover, at room temperature (Not exceeding 28°C), out of direct sunlight and protect from extreme temperatures. Shelf life is up to 2 years when stored as per above conditions.



Ceyalac (Pvt) Ltd.

📍 #10 (1st Floor), School Lane,
Colombo 03, Sri Lanka.
📞 +94 11 7222252
📠 +94 11 2507770
✉️ info@ceyalac.com
🌐 www.ceyalac.com

Sales Hotline: 773 833 929