

CEYAKRETE

construction chemicals & coatings

TOUGHSEAL

SINGLE PART
WATERPROOF
COATING



USES

WATER TANKS, SLABS, PONDS, ROOFTOPS,
BALCONIES, BATHROOMS, FLOWER TROUGHES, ETC.



EXCELLENT BONDING
STRENGTH



FIBRE
REINFORCED



ECONOMICAL &
HIGH WORKABILITY

TOUGHSEAL



CeyaKrete ToughSeal is a one-part, fiber-reinforced, cement-based waterproofing solution designed for internal and external use in both residential and commercial applications. Its advanced formulation incorporates a matrix binder and reinforcing fibers to deliver enhanced strength and flexibility, making it ideal for surfaces subject to minor movement or cracking.

Thanks to its fiber-reinforced composition, **ToughSeal** eliminates the need for additional reinforcing mesh, simplifying application and saving time. It forms a seamless, durable membrane that bonds well to concrete, masonry, and cement render. Once cured, it can be overlaid with screed, plaster, or tiles, making it a versatile solution for bathrooms, balconies, basements, and more.

CeyaKrete ToughSeal is also UV resistant, which means it can be left exposed without the need for a protective screed, offering additional convenience for outdoor applications. Easy to apply with a brush, roller, or spray, it provides reliable waterproofing performance with long-lasting durability.

INSTRUCTIONS FOR USE

SURFACE PREPARATION

The substrate should be clean and sound, free of dust, loose particles, grease, oil, etc. Fill all voids, cracks, edges and angles with suitable repair material, so that the prepared surface is sound.

MIXING AND APPLICATION

Mixing Ratio: 310-350ml Water : 1Kg ToughSeal Powder

Add about 70% of the required volume of water to the powder and mix using a slow speed mixer (300RPM) for 3 minutes. Add the remaining water to the mixture if required for ease of application. Mix sufficient material to use within 30-40 minutes.

Saturate the concrete's surface with clean water. Apply the first coat while the surface is still damp but no free standing water. Apply using a short stiff bristle brush. Leave to dry for 2-4 hours. The second coat should be applied at a 90-degree angle to the first.

COVERAGE

6-7 SQFT / KG at a thickness of 1mm
(Depending on substrate condition)

STORAGE AND SHELF LIFE

Store under cover, at room temperature (Not exceeding 28°C), out of direct sunlight and protect from extreme temperatures. Shelf life is up to 1 year when stored as per above conditions.

CLEANING & DISPOSAL

Clean all the tools with water after use.

HEALTH & SAFETY

Remove splashes from skin with soap and water. In case of contact with eyes rinse with water, seek medical advice.

DISCLAIMER

The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subject to change without prior notice.

